

(19) 日本国特許庁 (J P)

(12) 公開特許公報 (A)

(11) 特許出願公開番号

特開2001-25227

(P2001-25227A)

(43) 公開日 平成13年1月26日 (2001.1.26)

(51) Int.Cl. ⁷	識別記号	F I	テームト* (参考)
H 0 2 K 41/02		H 0 2 K 41/02	Z 5 F 0 3 1
B 2 3 Q 5/28		B 2 3 Q 5/28	B 5 F 0 4 6
G 0 3 F 7/20	5 2 1	G 0 3 F 7/20	5 2 1 5 H 6 0 3
H 0 1 L 21/027		H 0 1 L 21/68	K 5 H 6 0 9
21/68		H 0 2 K 3/24	C 5 H 6 4 1

審査請求 未請求 請求項の数 8 OL (全 6 頁) 最終頁に続く

(21) 出願番号 特願平11-194074

(22) 出願日 平成11年7月8日 (1999.7.8)

(71) 出願人 000001007

キヤノン株式会社

東京都大田区下丸子3丁目30番2号

(72) 発明者 松本 敏雄

東京都大田区下丸子3丁目30番2号キヤノン株式会社内

(72) 発明者 鎌田 重人

東京都大田区下丸子3丁目30番2号キヤノン株式会社内

(74) 代理人 100086287

弁理士 伊東 哲也 (外1名)


最終頁に続く

(54) 【発明の名称】 リニアモータ並びにこれを有するステージ装置および露光装置

(57) 【要約】

【課題】 リニアモータコイル表面の保護膜にダメージを与えることなく、コイルを効率良く冷却し、このリニアモータを用いた装置の性能向上を図る。

【解決手段】 コイルと該コイルを覆い内部空間に冷媒が供給されるジャケットを有するリニアモータにおいて、該ジャケットを内側ジャケットと外側ジャケットからなる二重ジャケット構造とし、コイルの内側ジャケットと外側ジャケットに性質の異なる二種類の冷媒を流す。



【特許請求の範囲】

【請求項1】 コイルと該コイルを覆い内部空間に冷媒が供給されるジャケットを有するリニアモータにおいて、該ジャケットを内側ジャケットと外側ジャケットとからなる二重ジャケット構造とし、コイルの内側ジャケットと外側ジャケットに性質の異なる二種類の冷媒を流すことを特徴とするリニアモータ。

【請求項2】 前記内側ジャケットに供給する冷媒が不活性冷媒であることを特徴とする請求項1記載のリニアモータ。

【請求項3】 前記二重ジャケットは、前記コイルを固定するためのフレームと該フレームを挟んで該リニアモータの駆動方向に対し両側面に各々二枚のシートを重ねて接合して形成されたものである請求項1または2記載のリニアモータ。

【請求項4】 前記二重ジャケットは、非磁性体材料であって電気的高抵抗材または絶縁体材料からなることを特徴とする請求項1～3のいずれかに記載のリニアモータ。

【請求項5】 前記二重ジャケットを挟んで前記コイルに対向する磁石が取り付けられたヨークが設けられていることを特徴とする請求項1～4のいずれかに記載のリニアモータ。

【請求項6】 請求項1～5のいずれかに記載のリニアモータを駆動機構として有することを特徴とするステージ装置。

【請求項7】 請求項6記載のステージ装置で基板を搭載し該基板に露光を行う手段を有することを特徴とする露光装置。

【請求項8】 請求項7記載の露光装置を用いてデバイスを製造することを特徴とするデバイス製造方法。

【発明の詳細な説明】

【0001】

【発明の属する技術分野】本発明は、例えば半導体露光装置や高精度加工機など精密な位置決めを行うための装置などに好適に使用されるリニアモータに関するものである。

【0002】

【従来の技術】半導体露光装置や高精度加工機などで使用されるナノメートルオーダーの位置決め装置では、駆動源であるリニアモータからの発熱が位置決めに影響を及ぼす。発熱による構造体の熱変形あるいは空気温度の上昇による位置計測のレーザ干渉計の計測誤差などの要因によって、リニアモータの搭載された装置の位置決め精度が悪化する。例えば、1℃の温度変化であっても100mmの低熱膨張材（熱膨張係数 1×10^{-6} ）は100nmだけ変形するし、また、光干渉式測長計の光路における空気温度の変化が1℃以下であっても測定値に100nmの誤差が生じ得る。従って、これらの温度変化の防止策としてリニアモータの冷却、特にリニアモータから発生する熱の回収が必要となっている。

【0003】一方、装置の高性能化に伴い、リニアモータの高出力化が要求されており、そのためにコイルに流れる電流を増やすと発熱量も大きく増大する。よってさらなる冷却能力の増強が必要とされる。また、コイル温度の上昇によるコイル抵抗の増加やコイル線の破損を防ぐためにも、コイルの冷却能力を高めることは重要である。

【0004】図4は冷却手段を備えた従来のリニアモータの構成を示す図である。同図のリニアモータは、コイル1とその両側のヨーク2に固定された永久磁石3、3'により構成され、コイル1は肉薄のシート4、4'およびフレーム5で構成されたジャケット8で覆われている。コイル1は固定具7によってフレーム5に固定されている。ここでジャケット8の内部空間6に冷媒を流すことにより、コイルからの発生熱を回収している。

【0005】

【発明が解決しようとする課題】上記従来例において、冷媒の流量を一定にしてコイルの冷却能力を上げるためには、冷媒に熱の吸収効率の高いものを使うと有効であるが、反面冷媒は高圧電流の流れているコイルに直接に接しているため、活性化した冷媒であると、コイル表面の保護膜が破損し電気的な絶縁破壊が起こりリニアモータの機能を失う恐れがある。これを防ぐため化学的に不活性な冷媒をコイル冷却に用いているが、一般的に不活性冷媒は熱の吸収効率が悪く、リニアモータの出力をさらに上げるために大電力を流すと、冷却能力が不足する可能性があった。

【0006】本発明は、上記課題を解決するためのもので、リニアモータコイル表面の保護膜にダメージを与えることなくコイルからの発熱を効率良く除去することで位置決め精度に及ぼす影響、構造体の熱変形、レーザ干渉計の計測誤差等をなくし、このリニアモータを使用した優れたステージ装置や露光装置、デバイス製造方法などを提供することを目的とする。

【0007】

【問題を解決するための手段】上記目的を達成するため、本発明では、コイルと該コイルを覆い内部空間に冷媒が供給されるジャケットを有するリニアモータにおいて、該ジャケットを内側と外側との二重構造とし、コイルの内側ジャケットと外側ジャケットに性質の異なる二種類の冷媒を流すことを特徴とする。このような二重ジャケットは、例えばコイルと該コイルを覆い内部空間に冷媒が供給されるジャケットを有する従来のリニアモータに対し、該ジャケットの外側に冷媒が供給される外側ジャケットを付加することにより得られる。内側ジャケットには、コイル表面の保護膜を破損させないよう不活性冷媒を流す。外側ジャケットには、活性、不活性にかかわらず冷却効率の良い冷媒を流す。

【0008】本発明のステージ装置は、上記構成のリニ

アモータを駆動機構として有することを特徴とするものであり、本発明の露光装置は上記ステージ装置で基板を搭載して、該基板に露光を行う手段を有することを特徴とするものである。また本発明のデバイス製造方法は上記露光装置を用いてデバイスを製造することを特徴とするものである。

【0009】

【作用】本発明によれば、コイル内側ジャケットに不活性冷媒を使用して、コイル表面の絶縁層にダメージを与えることを防止している。また、コイル内側ジャケットに一般的に冷却能力の劣る不活性冷媒を使用したことによる冷却能力の不足を、二重ジャケットの外側ジャケットに冷却効率の良い冷媒を流すことにより、補うことができる。よって、本発明によれば、コイル表面の絶縁層にダメージを与えることなくリニアモータコイルからの発熱を吸収し、精度に及ぼす影響、構造体の熱変形、レーザ干渉計の計測誤差等をなくし、このリニアモータを使用した優れたステージ装置や露光装置、デバイス製造方法などを提供することができる。

【0010】

【実施例】（実施例1）図1は本発明の一実施例に係る単相リニアモータの構成を表す図である。図2は図1のリニアモータの内部構造を説明する分解図、図3は図1のリニアモータの斜視図である。

【0011】図1において、1は駆動用の電流が流れるコイル、2は磁気回路を構成する2つのヨーク、3は各ヨーク2に固定され異なる磁気同士が互いに対向して配置された永久磁石である。4、4'はコイル1を挟んで配されたシート、5は2枚のシート4、4'同士を支持するフレームであり、該シート4、4'とフレーム5によって、コイル1を内包する内側ジャケットを構成している。6は該内側ジャケットの内部空間であり、7はコイル1をフレーム5に固定している固定具である。9、9'は本実施例の特徴部材である二重ジャケットの外側ジャケットを構成する部材であり、10は該外側ジャケットの内部空間である。シート4、4'および9、9'とフレーム5との接合は接着剤やボルトなどで固定されている。シート4、4'、フレーム5、シート9、9'の材質は非磁性体材料であり、また電気的高抵抗材または絶縁体材料、例えば高分子樹脂材料またはセラミックス材料が好ましい。

【0012】図2および図3において、20はコイル1のリード線（2本）、21はリード線20をジャケット内部から外部へ引出すための小孔である。この小孔21から冷媒が漏れ出さないように、リード線を引き出した後に接着剤等で小孔が気密に封止されている。22および23は内側ジャケットに接続された冷媒の供給管および回収管である。冷媒は供給管22から供給されて内側ジャケット内を流れコイルの発熱熱を受け取り、回収管23から回収される。コイル1の導線自体が直接冷媒に

触れないようコイル表面には保護膜が形成されているが、保護膜にダメージを与えないために、冷媒は液体または気体であっても不活性冷媒を供給する。24および25は外側ジャケットに接続された冷媒の供給管および回収管である。冷媒は供給管24から供給されて外側ジャケット内を流れ、内側ジャケットを流れている冷媒から、シート4、4'を介してコイルの発熱を受け取り、回収管25から回収される。外側ジャケットに供給する冷媒は、液体または気体であってもよい。また不活性冷媒である必要はないが、熱の吸収効率の高いものが好ましい。

【0013】上記構成において、固定磁界を発生している永久磁石3、3'の間の空間に位置するコイル1に電流を流すとローレンツ力が働き、コイル1と永久磁石3、3'は図1の紙面内上下方向に相対的に運動する。例えば、同図の上側半分においては、磁界は紙面の左から右方向へ、電流が紙面の奥から手前方向に流れると、電流の大きさに応じた力がコイル1には紙面の上方へ永久磁石3、3'には下方へ働き、それぞれが相対的に移動する。このようにコイルに所定の電流を流すことにより、ヨーク（すなわち永久磁石3、3'）およびコイルがそれぞれ固定されている構造物を駆動するものである。なお、本実施例ではコイル1がフレーム5に固定されており、コイル側が固定子、永久磁石が保持されたヨーク側が可動子となつたいわゆるムービングマグネット型のリニアモータとなっているが、固定子と可動子が逆であってもよい。また、図1ではコイル1は固定具7によってフレーム5に固定しているが、シート4、4'に固定するようにしてもよい。

【0014】（実施例2）図5は実施例1で説明したリニアモータを用いたウエハステージを有する露光装置の一例を示す。同図において、51はあおり機構を有するウエハステージ天板（あおりステージ）であり、上面に半導体ウエハ53を搭載している。あおりステージ51の上方には、光源や照明光学系を有する照明系57、ウエハに転写すべきパターンを備えたレチクル58、該レチクル58のパターンを所定の倍率で縮小投影する縮小投影光学系59が設けられている。

【0015】ウエハステージの構成について説明する。54はあおりステージ51を水平方向のみ規制するガイドであり、例えば静圧軸受を用いることによって、Z方向、傾斜方向およびZ軸回転方向の運動を許容している。56はベースである。55は上記説明した実施例1の構成を備えたリニアモータであり、3個のリニアモータ（残りの1個は図示せず）の駆動によって、ステージ51の重力方向であるZ方向の位置あるいは傾きをベース56に対して調節することができる。また、ステージ51のZ方向の位置および傾きを計測することにより、ウエハステージとしてのZ方向の位置および傾きを制御できる。

【0016】本実施例によれば、リニアモータの冷却効率が上がり、コイルから発生する熱のほぼ全量を回収しているため、リニアモータ25a、25bからの発熱がステージ51に伝わって温度上昇させたり、雰囲気温度を上昇させることがないため、ウエハステージの位置決め精度を飛躍的に向上させることができ、ひいては従来以上に高精度な露光転写が可能となる。

【0017】(実施例3) 図6は上記露光装置を使用した半導体デバイス(ICやLSI等の半導体チップ、あるいは液晶パネルやCCD等)の生産フローを示す。ステップ1(回路設計)では半導体デバイスの回路設計を行う。ステップ2(マスク製作)では設計した回路パターンを形成したマスクを製作する。ステップ3(ウエハ製造)ではシリコン等の材料を用いてウエハを製造する。ステップ4(ウエハプロセス)は前工程と呼ばれ、上記用意したマスクとウエハを用いて、リソグラフィ技術によってウエハ上に実際の回路を形成する。ステップ5(組み立て)は後工程と呼ばれ、ステップ4によって作製されたウエハを用いて半導体チップ化する工程であり、アセンブリ工程(ダイシング、ボンディング)、パッケージング工程(チップ封入)等の工程を含む。ステップ6(検査)ではステップ5で作製された半導体デバイスの動作確認テスト、耐久性テスト等の検査を行う。こうした工程を経て半導体デバイスが完成し、これが出荷(ステップ7)される。

【0018】図7は上記ウエハプロセスの詳細なフローを示す。ステップ11(酸化)ではウエハの表面を酸化させる。ステップ12(CVO)ではウエハ表面に絶縁膜を形成する。ステップ13(電極形成)ではウエハに電極を蒸着によって形成する。ステップ14(イオン打ち込み)ではウエハにイオンを打ち込む。ステップ15(レジスト処理)ではウエハに感光剤を塗布する。ステップ16(露光)では上記説明した露光装置によってマスク回路パターンをウエハに焼付露光する。ステップ17(現像)では露光したウエハを現像する。ステップ18(エッチング)では現像したレジスト像以外の部分を削り取る。ステップ19(レジスト剥離)ではエッチン

グが済んで不要となったレジストを取り除く。これらのステップを繰り返すことによって、ウエハ上に多重に回路パターンが形成される。

【0019】

【発明の効果】本発明によれば、コイルのジャケットを二重ジャケット構造にしてコイル内側ジャケットに不活性冷媒を流すことでコイル表面の保護膜にダメージを与えることなく一次冷却を行い、一般的に熱の吸収効率の悪い不活性冷媒を流した一次冷却で完全に除去できなかった熱を外側ジャケットで二次冷却することにより、総合的に冷却効率を上げることができるようになった。その結果コイルに、より大電力を流すことが可能となり、リニアモータの推力向上によるステージ装置の高速化が実現できた。またコイルからの発熱を少なくすることができたので、ステージ装置の熱による構造体の熱変形、レーザー干渉計の計測誤差を少なくすることができステージ装置の精度向上ができた。

【図面の簡単な説明】

【図1】 本発明の実施例1に係るリニアモータを説明する上面図である。

【図2】 図1のリニアモータのジャケット構成を示す分解図である。

【図3】 図1のリニアモータの外観を表す斜視図である。

【図4】 従来例のリニアモータを説明する上面図である。

【図5】 本発明の実施例2に係るステージを有する露光装置の構成図である。


【図6】 本発明の実施例3に係る半導体デバイスの製造フローを示す図である。

【図7】 図6のウエハプロセスの詳細なフローを示す図である。


【符号の説明】

1: コイル、2: ヨーク、3、3': 永久磁石、4、4': 内側ジャケットシート、5: フレーム、7: 固定具、9、9': 外側ジャケットシート。


【図1】




【図2】




【図3】




【図4】




【図5】



【図6】



【図7】



フロントページの続き

(51)Int. Cl.⁷H02K 3/24
9/00

識別記号

FI

H02K 9/00
H01L 21/30

テーマコード(参考)

Z
503A

Fターム(参考) 5F031 CA02 CA05 FA01 FA02 FA07
 GA64 HA38 HA53 JA01 KA06
 KA07 LA08 MA27 PA11 PA30
 5F046 CC01
 5H603 AA12 AA13 BB01 BB09 BB15
 CA01 CA02 CA05 CB01 CC19
 5H609 BB08 PP02 PP05 PP08 QQ07
 RR32 RR74
 5H641 BB06 BB18 BB19 GG02 GG03
 GG05 GG07 GG11 GG12 GG15
 HH02 HH03 HH05 JB02 JB05

*** NOTICES ***

Japan Patent Office is not responsible for any damages caused by the use of this translation.

- 1.This document has been translated by computer. So the translation may not reflect the original precisely.
- 2.**** shows the word which can not be translated.
- 3.In the drawings, any words are not translated.

DESCRIPTION OF DRAWINGS

[Brief Description of the Drawings]

[Drawing 1] It is a plan explaining the linear motor concerning the example 1 of this invention.

[Drawing 2] It is the exploded view showing the jacket configuration of the linear motor of drawing 1 .

[Drawing 3] It is a perspective view showing the appearance of the linear motor of drawing 1 .

[Drawing 4] It is a plan explaining the linear motor of the conventional example.

[Drawing 5] It is the block diagram of the aligner which has a stage concerning the example 2 of this invention.

[Drawing 6] It is drawing showing the manufacture flow of the semiconductor device concerning the example 3 of this invention.

[Drawing 7] It is drawing showing the detailed flow of the wafer process of drawing 6 .

[Description of Notations]

1: A :permanent magnet, and coil, 2:Yolk, 3, and 3 '4, 4':inside jacket sheet, 5:frame, 7:fastener, 9, 9' : outer jacket sheet.

[Translation done.]

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2001-025227

(43)Date of publication of application : 26.01.2001

(51)Int.Cl.

H02K 41/02
B23Q 5/28
G03F 7/20
H01L 21/027
H01L 21/68
H02K 3/24
H02K 9/00

(21)Application number : 11-194074

(71)Applicant : CANON INC

(22)Date of filing : 08.07.1999


(72)Inventor : MATSUKI TOSHIO
KAMATA SHIGETO

(54) LINEAR MOTOR, AND STAGE SYSTEM AND ALIGNER PROVIDED WITH THE MOTOR

(57)Abstract:

PROBLEM TO BE SOLVED: To efficiently remove heat from a linear motor coil without damaging protective film on the surface of the coil by providing a jacket with double structure composed of an inner jacket and an outer jacket and letting different types of coolants to flow through the inner jacket and the outer jacket of the coil.

SOLUTION: A double jacket is constituted, for example, of a coil inner jacket 4 and 4' which embraces a coil 1 and is supplied in its internal space with a coolant and an outer jacket 9 and 9', which is supplied outside the jacket with coolant. Inert gas is let to flow through the coil inner jacket 4 and 4' so that the protective film on the coil is not damaged. A coolant, regardless of its being activated or inert, satisfactory in cooling efficiency is let to flow through the outer jacket 9 and 9'. Thus insufficiency in cooling capability due to adoption of an inert coolant inferior in cooling capability for the coil inner jacket 4 and 4' can be made up by letting coolant satisfactory in cooling efficiency flow through the jacket 9 and 9'.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office


* NOTICES *

Japan Patent Office is not responsible for any damages caused by the use of this translation.


1. This document has been translated by computer. So the translation may not reflect the original precisely.
2. **** shows the word which can not be translated.
3. In the drawings, any words are not translated.

DRAWINGS


[Drawing 1]




[Drawing 2]




[Drawing 3]




[Drawing 4]



[Drawing 5]



[Drawing 6]



[Drawing 7]

* NOTICES *

Japan Patent Office is not responsible for any damages caused by the use of this translation.

1. This document has been translated by computer. So the translation may not reflect the original precisely.
2. **** shows the word which can not be translated.
3. In the drawings, any words are not translated.

DETAILED DESCRIPTION

[Detailed Description of the Invention]

[0001]

[Field of the Invention] This invention relates to the linear motor used suitable for the equipment for performing precise positioning, such as for example, a semi-conductor aligner and a high precision processing machine, etc.

[0002]

[Description of the Prior Art] In the pointing device of the nano meter order used with a semi-conductor aligner, a high precision processing machine, etc., generation of heat from the linear motor which is a driving source has a bad influence on positioning. According to factors, such as heat deformation of the structure by generation of heat, or a measurement error of the laser interferometer of the location measurement by the rise of air temperature, the positioning accuracy of the equipment with which the linear motor was carried gets worse. For example, even if it is a 1-degree C temperature change, a 100mm low-thermal expansive additive (coefficient of thermal expansion 1×10^{-6}) transforms only 100nm, and even if change of the air temperature in the optical path of an optical interference type length measurement meter is 1 degree C or less, a 100nm error may arise in measured value. Therefore, cooling of a linear motor, especially recovery of the heat generated from a linear motor are needed as a preventive measure of these temperature changes.

[0003] If the current which the high increase in power of a linear motor is demanded, therefore flows in a coil with high-performance-izing of equipment on the other hand is increased, calorific value will also increase greatly. Therefore, enhancement of the further refrigeration capacity is needed. Moreover, also in order to prevent the increment in coil resistance and the breakage of a coil line by the rise of coil temperature, it is important to heighten the refrigeration capacity of a coil.

[0004] Drawing 4 is drawing showing the configuration of the conventional linear motor equipped with the cooling means. The linear motor of this drawing is constituted by a coil 1, the permanent magnet 3 fixed to York 2 of the both sides, and 3', and the coil 1 is covered in the jacket 8 which consisted of a sheet 4 of closing in, 4', and a frame 5. The coil 1 is being fixed to the frame 5 by the fastener 7. The generating heat from a coil is collected by pouring a refrigerant to the building envelope 6 of a jacket 8 here.

[0005]

[Problem(s) to be Solved by the Invention] There is a possibility of the protective coat on the front face of a coil being damaged as it is the activated refrigerant since the opposite side refrigerant is directly in contact with the coil with which high tension current is flowing, and electric dielectric breakdown happening although it is effective if what has the high absorption efficiency of heat is used for a refrigerant in order to fix the flow rate of a refrigerant and to improve the refrigeration capacity of a coil in the above-mentioned conventional example, and losing the function of a linear motor. In order to prevent this, the inactive refrigerant was chemically used for coil cooling, but generally, in order that the absorption efficiency of heat might be bad and might raise the output of a linear motor further, when large power was passed, refrigeration capacity may have been insufficient for the inactive refrigerant.

[0006] This invention is for solving the above-mentioned technical problem, abolishes the effect which exerts generation of heat from a coil on positioning accuracy by removing efficiently, heat deformation of the structure, the measurement error of a laser interferometer, etc., without giving a damage to the protective coat of a linear motor coil front face, and aims at offering the outstanding stage equipment which used this linear motor, an aligner, the device manufacture approach, etc.

[0007]

[Means for Solving the Problem] In order to attain the above-mentioned purpose, in this invention, in the linear motor which has the jacket with which a coil and this coil are covered and a refrigerant is supplied to a building envelope, this jacket is made into the dual structure of the inside and an outside, and it is characterized by pouring two kinds of refrigerants with which properties differ in the inside jacket and outer jacket of a coil. Such a duplex jacket is obtained by adding the outer jacket with which a refrigerant is supplied to the outside of this jacket to the conventional linear motor which has the jacket with which a coil and this coil are covered and a refrigerant is supplied to a building envelope. In an inside jacket, an inactive refrigerant is poured so that the protective coat on the front face of a coil may not be damaged. In an outer jacket, a refrigerant with sufficient cooling effectiveness is poured irrespective of activity and inactive.

[0008] The stage equipment of this invention is characterized by having the linear motor of the above-mentioned configuration as a drive, and it is characterized by for the aligner of this invention carrying a substrate with the above-mentioned stage equipment, and having the means exposed to this substrate. Moreover, the device manufacture approach of this invention is characterized by manufacturing a device using the above-mentioned aligner.

[0009]

[Function] According to this invention, it has prevented using an inactive refrigerant for a coil inside jacket, and giving a damage to the insulating layer on the front face of a coil. Moreover, the outer jacket of a duplex jacket is suppliable with lack of the refrigeration capacity by having used the inactive refrigerant in which refrigeration capacity is generally inferior in a coil inside jacket by pouring a refrigerant with sufficient cooling effectiveness. Therefore, according to this invention, generation of heat from a linear motor coil can be absorbed without giving a damage to the insulating layer on the front face of a coil, the effect and the heat deformation of the structure which are exerted on precision, the measurement error of a laser interferometer, etc. can be abolished, and the outstanding stage equipment which used this linear motor, an aligner, the device manufacture approach, etc. can be offered.

[0010]

[Example] (Example 1) Drawing 1 is drawing showing the configuration of the single phase linear motor concerning one example of this invention. The exploded view and drawing 3 drawing 2 explains the internal structure of the linear motor of drawing 1 to be are the perspective view of the linear motor of drawing 1.

[0011] In drawing 1, the coil with which the current for a drive in 1 flows, two York where 2 constitutes a magnetic circuit, and 3 are permanent magnets with which MAG which are fixed to each York 2 and are different countered mutually, and they have been arranged. The sheet with which 4 and 4' was allotted on both sides of the coil 1, and 5 are the sheet 4 of two sheets, and a frame which supports 4', and the inside jacket which connotes a coil 1 by this sheet 4, and 4' and a frame 5 is constituted. 6 is the building envelope of this inside jacket, and 7 is a fastener which is fixing the coil 1 to a frame 5. 9 and 9' is a member which constitutes the outer jacket of the duplex jacket which is the description member of this example, and 10 is the building envelope of this outer jacket. Junction on sheet 4, 4' and 9, and 9' and a frame 5 is being fixed with adhesives, a bolt, etc. a sheet -- four -- four -- ' -- a frame -- five -- a sheet -- nine -- nine -- ' -- the quality of the material -- a non-magnetic-material ingredient -- it is -- moreover, electric high resistance material, an insulator ingredient, for example, a macromolecule resin ingredient, or a ceramic ingredient -- being desirable.

[0012] In drawing 2 and drawing 3, it is a stoma for 20 pulling out lead wire 20 to the lead wire (2) of a coil 1, and pulling out 21 from the interior of a jacket to the exterior. After pulling out lead wire so that a refrigerant may not begin to leak from this stoma 21, the closure of the stoma is airtightly carried out with adhesives etc. 22 and 23 are the supply pipes and recovery tubing of a refrigerant which were connected to the inside jacket. A refrigerant is supplied from a supply pipe 22, and flows the inside of an inside jacket, and the generating heat of a coil is collected from reception and the recovery tubing 23. The protective coat is formed in the coil front face so that the lead wire of a coil 1 itself cannot touch a direct refrigerant, but in order not to give a damage to a protective coat, even if a refrigerant is a liquid or a gas, it supplies an inactive refrigerant. 24 and 25 are the supply pipes and recovery tubing of a refrigerant which were connected to the outer jacket. Refrigerants are collected from reception and the recovery tubing 25 in generation of heat of a coil through the sheet 4 from the refrigerant which is supplied from a supply pipe 24, flows the inside of an outer jacket, and is flowing the inside jacket, and 4'. The refrigerant supplied to an outer jacket may be a liquid or a gas. Moreover, although it is not necessary to be an inactive refrigerant, what has the high absorption efficiency of heat is desirable.

[0013] In the above-mentioned configuration, if a current is passed in the permanent magnet 3 which has generated the fixed field system, and the coil 1 located in the space between 3', the Lorentz force will work and a coil 1, a permanent magnet 3, and 3' will exercise relatively [direction / of drawing 1 / in space / vertical]. For example, in the top one half of this drawing, if a current flows in the direction of this side from the back of space rightward from the left of space, the force according to the magnitude of a current will work to above [of space] in a coil 1, and will work downward to a permanent magnet 3 and 3', and each will move a field relatively. Thus, by passing a predetermined current in a coil, the structure with which York (namely, a permanent magnet 3, 3') and a coil are being fixed, respectively is driven. In addition, a stator and a needle may be reverse, although the coil 1 is being fixed to the frame 5 and the coil side serves as the so-called MUBINGU magnet type with which the York side where the stator and the permanent magnet were held became a needle of linear motor in this example. Moreover, although it is fixing to a frame 5 with the fastener 7, you may make it fix a coil 1 to a sheet 4 and 4' in drawing 1.

[0014] (Example 2) Drawing 5 shows an example of an aligner which has a wafer stage using the linear motor explained in the example 1. In this drawing, 51 is a wafer stage top plate (gate stage) which has a gate device, and carries the semi-conductor wafer 53 in the top face. The contraction projection optics 59 which carries out contraction projection of the pattern of the illumination system 57 which has the light source and an illumination-light study system above the gate stage 51, the reticle 58 equipped with the pattern which should be imprinted to a wafer, and this reticle 58 for a predetermined scale factor is established.

[0015] The configuration of a wafer stage is explained. 54 is a guide which carries out horizontal chisel regulation of the gate stage 51, for example, permits movement of a Z direction, the inclination direction, and zeta shaft hand of cut by using a hydrostatic bearing. 56 is the base. 55 is the linear motor equipped with the configuration of an example 1 which gave above-mentioned] explanation, and can adjust the location or inclination of the direction of zeta which is the gravity direction of a stage 51 to the base 56 by the drive of three linear motors (the one remaining pieces are not shown). Moreover, the location and inclination of the direction of zeta as a wafer stage are controllable by measuring the location and inclination of the direction of zeta of a stage 51.

[0016] According to this example, since the whole quantity is collected mostly and there is nothing of the heat which the cooling effectiveness of a linear motor goes up and is generated from a coil for which generation of heat from linear motors 25a and 25b gets across to a stage 51, and carries out a temperature rise, or raises ambient temperature, the positioning accuracy of a wafer

stage can be raised by leaps and bounds, as a result a highly precise exposure imprint than before is attained.


[0017] (Example 3) Drawing 6 shows the production flow of the semiconductor devices (semiconductor chips, such as IC and LSI, or a liquid crystal panel, CCD, etc.) which used the above-mentioned aligner. The circuit design of a semiconductor device is performed at step 1 (circuit design). The mask in which the designed circuit pattern was formed is manufactured at step 2 (mask manufacture). At step 3 (wafer manufacture), a wafer is manufactured using ingredients, such as silicon. Step 4 (wafer process) is called a last process, and forms an actual circuit on a wafer with a lithography technique using the mask and wafer which carried out [above-mentioned] preparation. Step 5 (assembly) is called a back process, is a process semiconductor-chip-ized using the wafer produced by step 4, and includes processes, such as an assembly process (dicing, bonding) and a packaging process (chip enclosure). At step 6 (inspection), the check test of the semiconductor device produced at step 5 of operation, an endurance test, etc. are inspected. A semiconductor device is completed through such a process and this is shipped (step 7).

[0018] Drawing 7 shows the detailed flow of the above-mentioned wafer process. The front face of a wafer is oxidized at step 11 (oxidation). An insulator layer is formed in a wafer front face at step 12 (CVO). At step 13 (electrode formation), an electrode is formed in a wafer by vacuum evaporation. Ion is driven into a wafer at step 14 (ion implantation). A sensitization agent is applied to a wafer at step 15 (resist processing). At step 16 (exposure), printing exposure of the mask circuit pattern is carried out at a wafer with the aligner which gave [above-mentioned] explanation. The exposed wafer is developed at step 17 (development). At step 18 (etching), parts other than the developed resist image are shaved off. The resist which etching could be managed with step 19 (resist exfoliation), and became unnecessary is removed. By carrying out by repeating these steps, a circuit pattern is formed on a wafer multiplex.

[0019]

[Effect of the Invention] Cooling effectiveness can be synthetically gathered now by performing the primary cooling of concrete, without giving a damage to the protective coat on the front face of a coil by according to this invention, making the jacket of a coil into duplex jacket structure, and pouring an inactive refrigerant in a coil inside jacket, and carrying out the secondary cooling of concrete of the heat which was not able to be completely removed by the primary cooling of concrete which generally poured the inactive refrigerant with the bad absorption efficiency of heat with an outer jacket. As a result, it became possible to pass large power more in a coil, and improvement in the speed of the stage equipment by the improvement in a thrust of a linear motor has been realized. Moreover, since generation of heat from a coil was lessened, heat deformation of the structure by the heat of stage equipment and the measurement error of a laser interferometer could be lessened, and improvement in precision of stage equipment was completed.

[Translation done.]



[Translation done.]